



**Notes**

1. The dimension 45.0, of the exposed shaft length is a recommended minimum for ease of assembly. The dimension can be reduced to 32.0, but the assembly procedure will be made fiddly.

Issue 1	09/02/01	Initial Layout	Total Tension Solutions Ltd. 14 Highpoint Business Village Henwood Industrial Estate Ashford Kent. TN24 8DH  Telephone: +44 (0) 1233 624422 Fax: +44 (0) 1233 624466 E-Mail: info@tts-systems.co.uk	<b>TITLE</b>  SIZE 2 CRF / CRL CARTRIDGE TRANSDUCER WITH TAPER LOCK SCREW MOUNT GENERAL ARRANGEMENT	Drawn By	Date	Approved	Date	Scale	Projection	Third Angle
Issue 2	19/06/01	Added detail			CJ	09/02/01	XXX	XX/XX/XX	N.T.S	Tolerance	+/-0.1 unless otherwise stated
Issue 3	04/03/06	One piece beam design			DRAWING NUMBER		222-2-5		Material	N/A	
Issue 4	08/06/06	Connector fixings moved			CUSTOMER REFERENCE				Finish	N/A	
Issue 5	03/12/06	Title change and Lumberg conn.							Notes	See above	
Issue 6	XX/XX/XX	XXXXXXXXXXXXXXXXXXXXXXXXXXXX									
Issue 7	XX/XX/XX	XXXXXXXXXXXXXXXXXXXXXXXXXXXX									
Issue 8	XX/XX/XX	XXXXXXXXXXXXXXXXXXXXXXXXXXXX									